About p.mapper

The p.mapper framework is intended to offer broad functionality and multiple configurations in order to facilitate the setup of a MapServer application based on PHP/MapScript. Functions included are:

- DHTML (DOM) zoom/pan interface (no use of frames)
- Fully featured query functions (identify, select, search)
- Very flexible configuration of functions, behaviour and layout
- Multilingual user interface
  pre-defined: EN, DE, IT, FR, NL, SK, ES, RU, BR, HR, HU, ZH, JA, BG, CZ, EL, HE, LV, CAT, ID, TW
- Plugin API to add custom functionality

Read more >>>

Documentation

- p.mapper Readme First
- Quick install instructions v4.x
- p.mapper manual v4.x
  - GUI layout configuration
  - XML file settings
  - JavaScript settings
  - Search definition via XML file
  - Printing parameters in XML file
  - Available plugins
- Upgrade information
- Packages for Debian&Ubuntu and MS4W
- Change Log for p.mapper releases
- Older documentation for v3.x

FAQ

- Problems and debugging
- Configuration and settings
- Tips and tricks
- Customizations (Plugins, JS, CSS)

User Portal

- User wishlist

Acknowledgements

For acknowledgements please see here

Use of this Wiki and Ticket system

Permission to comment and contribute to this wiki as well as open a Ticket for p.mapper requires registration. Due to beginning spam the **self-registration** functionality is just **temporarily enabled**. Please contact me via mail if you would like to contribute to this Wiki and I will send you a username and

password or enable the registration function for some time. Note that all accounts with no registration at the p.mapper mailing list will be removed.